




Square

Leds C4 Team

TC-0434-BLA

Downlight IP40 Square LED 35.4W 3000K Blanco 3226lm

TECHNICAL FEATURES



Substitución directa placas tipo armstrong
Directly replacing armstrong ceiling units

Power (W) : 35.4W

Total power consumption of light (W) : 40.1W

Real lumens : 3226

Real lm/W : 80

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Dimming protocol : ON-OFF

Lens / reflector angle : HORIZONTAL 113°

UGR : <=22

Structure material : Aluminium

Structure finish : Blanco

Diffuser material : Acrylic

Diffuser finish : White

Voltage / frequency : 100-240V/50-60Hz

Power Factor : 0.90

Useful life : 36.000h L70B30

Warranty : 5 Years

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED

CRI: 80

MacAdam steps: 3



Photobiological risk: RG0

UGR

UGR crosswise: 20.6

UGR lengthwise: 20.9

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	20.6
UGR lengthwise	20.9



VENTILATION FEATURES

Power used: 40.1W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 2.04

Packaged weight (kg): 2.81

Packaging: 650mm x 40mm x 635mm



