

TECHNICAL CHARACTERISTICS

SBOBBB

# Bob




## Wood chair

Welcoming with smooth shapes, the Bob wood chair is inspired by the peacefulness of nature and the soul of the north to create pleasant, calm spaces, subtle yet contemporary. With its smooth wooden frame, it gives a warm and cozy touch to any space.

DESIGNED BY NADIA ARRATIBEL



**ondarreta**



### DIMENSIONS

46 cm x 54 cm x 82 cm x 47 cm (18.1" x 21.3" x 32.3" x 18.5") [width x depth x height x seat height]

### WEIGHT

4,2 kg (9,3 lb)

### PACKAGING

2 chairs per box, box dimensions:  
63 cm x 49 cm x 99 cm  
(24,8" x 19,3" x 39")

### CERTIFICATION

Product tested under the European standard EN 16139:2013, category of general use L1.

Designed in accordance with the Ecodesign standard UNE-EN ISO 14006: 2011 certified by AENOR.

### ACCESORIES

Felt glides

### ORIGIN

100% Made in Europe

### DESIGN

Nadia Arratibel



## **COMPONENTS**

### **FRAME**

#### **Material**

Solid Beech wood bowed with a singular method and CNC machined.

Medium density: 720 kg/m<sup>3</sup> (44.9 lb/ft<sup>3</sup>); Flex Strength: 1120 kg/cm<sup>2</sup>

(15,900 psi); Tensile Strength: 1210 kg/cm<sup>2</sup> (17,200 psi)

#### **Finish**

Stained or lacquered

### **SHELL**

#### **Beech**

Beech plywood board shell, 10 mm (0.4") thick. It's made with nine especially treated sheets, glued, pressed and CNC machined.

#### **Oak**

European Oak plywood board shell, 10 mm (0.4") thick.

#### **Fabrics**

8 mm (0.31") thick Beech plywood board shell. Medium density polyether stuffing foam.

#### **Combi (Beech + fabric)**

Two assembled Beech plywood sheets, upholstered front and varnished back (4 and 7 mm thick) (0.16" and 0.27"). Medium density polyether stuffing foam.

#### **Technical characteristics:**

Urea-formol glue: low formaldehyde emission (E1 European Normative)

The wood has the PEFC certificate.

#### **Finish**

Stained, lacquered, fabric or combi.

## **WOOD FINISHES**

### **STAIN**

Pigmented enamel with a transparent stain coating. Reactive drying paints: excellent adherence between layers and better mechanical resistance.

### **LACQUER**

Pigmented reactive drying lacquers.

#### **Technical characteristics:**

Satisfying UNE-EN 71-3 normative; Formaldehyde free compounds.

## **COM REQUIREMENTS**

Full fabric: 90 cm (35,4")

Combi: 90 cm (35,4")