Wireflow free-form



0356


Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. The electrical connection point can be positioned on the ceiling or wall.

Model Sheet







Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish 04 Black RAL 9005

LED temperature 2700 K / 3000 K / color 3500 K

Dimming Casambi / Push; 1-10V; DALI-2

Instalation type

Surface Canopy

Materials

Ceiling rose: Steel
Body: Aluminum
Rods: Steel

Light source

7 x LED 4,48W 350mA

D CRI>90 3432 lm 109 2700 K / 3500 K

Driver Constant Current 350 110~240 V V 50~60 Hz HZ

Dimmable LED IP20

Bi-volt 50-60Hz

Application Hanging lamps

Packaging 1 Box 0.42 m x 0.42 m x 0.25 m

Gross weigth 7 Net weigth 6 Vol. 0.0441


Lighting effect


General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data





 Efficiency
 40.11%

 Coordinate System
 CG

 Total Flux
 3432

 Maximum Value
 53.92

Other Applications

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty