




Ringo Ø110mm

PX-1000-INO

Recessed uplighting IP65/IP67 Ringo Ø110mm GU10 50W Stainless steel 525lm



TECHNICAL FEATURES



Power (W) : Max. power 50W

Total power consumption of light (W) : 50W

Real lumens : 525

Real lm/W : 11

Lens / reflector angle : MEDIUM 31°

UGR : <=22

Structure material : Stainless steel AISI304,
Aluminium

Structure finish : Stainless steel

Diffuser material : Glass

Diffuser finish : Transparent

Max. size of light bulb : 55/50 mm

Recommended light bulb : GU10

Voltage / frequency : 100-240V/50-60Hz



Warranty : 5 Years

Energy efficiency : Light bulb not included

LUMINOTECHNIC FEATURES

Lampholder: 1 x GU10

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	21.3
UGR lengthwise	21.3



VENTILATION FEATURES

Power used: 50W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 0.53

Packaged weight (kg): 0.64

Packaging: 115mm x 115mm x 155mm



