Wireflow free-form



0364


Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. The electrical connection point can be positioned on the ceiling or wall.

Model Sheet







Optional: Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish

O4 Black
RAL 9005

LED temperature 2700 K / 3000 K
color

Dimming

Materials

Ceiling rose: Steel
Body: Aluminum
Rods: Steel

Light source

4 x LED 4,48W 350mA

Push; 1-10V; DALI-2 / Casambi

CRI>80 1961 lm 109 2700 K / 3000 K

Driver Constant Current 350 110~240 V V 50~60 Hz HZ

Dimmable LED

[P20] Bi-volt 50-60Hz

Application Hanging lamps

Packaging 1 Box 0.42 m x 0.42 m x 0.25 m

Gross weigth 5.5 Net weigth 5 Vol. 0.0441


Lighting effect


Highlight

Lamp used to highlight a specific element.



Photometric Data





Efficiency 46.23%
Coordinate System CG
Total Flux 1961.10
Maximum Value 320.25

Other Applications

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty